

SPICE PARAMETER

EMD30

```
* EMD30_NPN NPN DT model
* Date: 2007/01/11
* BJT with resistors
*****C B E
.SUBCKT EMD30_NPN 1 2 3
R1 2 Base Rb 10k
R2 Base 3 Re 10k
Q1 1 Base 3 QDTC1
.MODEL Rb RES
+ R=1
.MODEL Re RES
+ R=1
.MODEL QDTC1 NPN
+ IS=20.000E-15
+ BF=198.80
+ VAF=15
+ IKF=.28787
+ ISE=20.001E-15
+ NE=1.6289
+ BR=8.4556
+ VAR=100
+ IKR=.2645
+ ISC=8.0686E-12
+ NC=2.3678
+ NK=.75224
+ RE=.2
+ RB=10.670
+ RC=1.1274
+ CJE=11.342E-12
+ MJE=.38289
+ CJC=4.0230E-12
+ MJC=.34629
+ TF=500.00E-12
+ XTF=580.91
+ VTF=195.13
+ ITF=19.351
+ TR=200.00E-9
+ XTB=1.5000
.ENDS EMD30_NPN
```

```
* EMD30_PNP PNP DT model
* Date: 2007/01/16
* BJT with resistors
*****C B E
.SUBCKT EMD30_PNP 1 2 3
R1 2 Base Rb 1k
R2 Base 3 Re 10k
Q1 1 Base 3 QDTB7
.MODEL Rb RES
+ R=1
.MODEL Re RES
+ R=1
.MODEL QDTB7 PNP
+ IS=110.00E-15
+ BF=304.37
+ VAF=10
+ IKF=.49747
+ ISE=110.00E-15
+ NE=1.5669
+ BR=126.93
+ VAR=100
+ IKR=8.1893
+ ISC=1.8816E-12
+ NC=1.2769
+ NK=.97427
+ RE=.1
+ RB=2.9741
+ RC=.56368
+ CJE=44.776E-12
+ MJE=.43395
+ CJC=8.9662E-12
+ MJC=.25891
+ TF=200.00E-12
+ XTF=374.33
+ VTF=37.015
+ ITF=6.7967
+ TR=10.000E-9
+ XTB=1.5000
.ENDS EMD30_PNP
```